

# ADHESIVE ID PLATE

User and Manual for application

# TARGHETTE ADESIVE

Istruzioni per applicazione



A.D.R. S.p.A.  
Via A.M. Ceriani, 96  
21040 UBOLDO - VA - ITALY  
Tel. +39 02 96 17 11  
Fax +39 02 96 17 14 20  
e-mail [adr@adraxles.com](mailto:adr@adraxles.com)  
p. IVA 00637410127

### BEFORE APPLICATION

**⚠ ATTENTION PLEASE :** Make sure the surface is well clean  
(by degrease product) and well dry.

Furthermore the surface must be free from Oxid, Calamine, Solid parts which don't guarantee the correct adhesion



### APPLICATION

Take off the ID Plate from the paper support and fix it on the axle/stub-axle by a heavy pressure (by roller tools) to avoid residual air remain between the surface and the ID Plate



EMISSION	EMISSION DATE	APPROVED	APPROVED DATE	REV.	PAGE
Quality Office	20.12.2017	Quality Group	20.12.2017	0	2 of 4



Do this step at least 6 times to let the glue works correctly.  
After the application wait at least 30 minutes before to over paint, protect heat termic stress,  
protect from water and all other products and external agents.  
In case of over painting, wait 48 hours before remove the upper protection film



EMISSION	EMISSION DATE	APPROVED	APPROVED DATE	REV.	PAGE
Quality Office	20.12.2017	Quality Group	20.12.2017	0	3 of 4

**RECOMMANDATIONS**

**⚠ PAY ATTENTION :** The ID Plate must not be remove and apply again  
The ID Plate must be fix on a flat surface on the BlackBull Axles.

The ID Plate must not be fixed on the Welding and not on the Radius

**BLACK BULL GOOD APPLICATION**

**BLACK BULL NO GOOD APPLICATION**



**⚠ WARNING :** In case of new application, order new ID Plate to ADR.  
ADR in not responsible for a not correct application

EMISSION	EMISSION DATE	APPROVED	APPROVED DATE	REV.	PAGE
Quality Office	20.12.2017	Quality Group	20.12.2017	0	4 of 4